

## Engelmann Calculator for Combined Heat Meters

# SensoStar C



- Compact design
- Battery easy to exchange; calculator prepared for 3 V power pack
- Inlet flow and outlet flow can be set on site
- Communication interfaces; can be added later to every device:

**LoRa + 3 pulse inputs;**

**Modbus RTU;**

**wireless M-Bus or wireless M-Bus + 3 pulse inputs;**

**M-Bus or M-Bus + 3 pulse inputs;**

**1 pulse output & 2 pulse outputs**

## Technical Data:

### *Calculator*

Temperature range medium heat	°C	0 – 150
Temperature range medium cooling	°C	0 – 50
Ambient temperature in the field	°C	5 – 55 at 95 % relative humidity
Transport temperature	°C	-25 – 70 (for maximal 168 h)
Storage temperature	°C	-25 – 55
Temperature difference range $\Delta\theta$ heat	K	3 – 100
Temperature difference range $\Delta\theta$ cooling	K	-3 – -50
Minimum temperature difference $\Delta\theta$ heat	K	> 0,05
Minimum temp. difference $\Delta\theta$ cooling	K	< -0,05
Minimum temperature difference	K	> 0,5 / < -0,5
$\Delta\theta_{HC}$ heat / cooling	°C	0,01
Resolution temperature	s	60 with a lifetime of 10 years; 30 with a lifetime of 6+1 years (optional); 2 using a power pack
Measuring cycle energy in normal operation	I/Imp	1; 2,5; 10; 25; 100; 250; 1000; 2500; adjustable (TX version) LCD – 8 digits + special characters up to 3 after comma MWh, kW, m <sup>3</sup> , m <sup>3</sup> /h (kWh, GJ); unit of energy can be set when the amount of energy is still ≤ 10 kWh optical interface (M-Bus protocol); optional: wireless M-Bus; wireless M-Bus + 3 pulse inputs; M-Bus; M-Bus + 3 pulse inputs; 1 pulse output; 2 pulse outputs; LoRa + 3 pulse inputs; Modbus RTU exchangeable 3 V lithium battery; prepared for 3 V power pack (input voltage 230 V; 24 V AC)
Pulse values, optional	years	10 (no option: 1 pulse output); 6+1 nonvolatile memory selectable yearly reading date; 15 monthly and semimonthly values: via display or wireless M-Bus (compact mode); 24 monthly and semimonthly values: via optical interface or M-Bus can be set individually; adding up energy or time flow, power and temperatures (inlet, outlet, $\Delta\theta$ ), plus the respective maximum values of the last 15 months
Display		IP54
Decimal places		yes
Units		M2 / E2
Interfaces		microcontroller CMOS input class IB according to EN 1434-2:2015 (D) water; optional, without approval*: water with a propylene glycol or ethylene glycol percentage rate of 20 %, 30 %, 40 % or 50 % (* type and concentration of glycol can be set at any time)
Power supply	kg	0,350
Estimated lifetime	mm	150 x 130 x 35
Data storage		
Reading dates		
2 tariff registers		
Storage of maximum values		
Protection class		
CE		
Mechanical / electromagnetic class		
Pulse input interface		
Medium		
Weight		
W x H x D		
<b>Flow meter requirements</b>		
Class of pulse output device		according to EN 1434-2:2015: OA (reed contact); OC (open collector)
Maximum input frequency	Hz	10
Pulse length and pulse pause		at least 25 ms pulse length; at least 50 ms pulse pause
<b>Temperature sensor requirements</b>		
Platinum precision resistor		Pt 500
Length of cables (unshielded)	m	up to 10 m in 2-wire technique; (3 and 10 available at Engelmann)
Installation		direct mounted; in temperature pockets